



Bel-Ray Company, Inc.

P.O. Box 526 • Farmingdale, New Jersey 07727 U.S.A.

TEL (732) 938-2421 • FAX (732) 938-4232

www.belray.com



BEL-RAY[®] NO-TOX[®] FILLER OIL 30

Bel-Ray No-Tox Filler Oil 30 was developed for use in systems found on container filling equipment typically encountered in the "clean" industries such as food, beverage, pharmaceutical and personal care products. It is ideal for use where water, juices, etc. are apt to wash off the lubricant.

Applications

- ◆ Container filling equipment

Features and Benefits

- ◆ NSF H1 registered Use where incidental food contact may occur.
- ◆ Oxidation inhibited Long term stability.

General Description

Bel-Ray No-Tox Filler Oil 30 is a water-white, tasteless and odorless lubricant for all filling machines requiring an SAE 30 oil that resists washout. **Bel-Ray No-Tox Filler Oil 30**, formulated with the highest quality USP white mineral oils and food grade additives, meets all NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved.

Product No. 62400

BEL-RAY[®] NO-TOX[®] FILLER OIL 30

TYPICAL PROPERTIES

<u>Product No.</u>	<u>62400</u>
Bel-Ray Name Grade	30
ISO Viscosity Grade	100
SAE Engine Oil Grade	30
Viscosity, ASTM D445	
@ 40°C, cSt	92.3
@ 100°C, cSt	10.7
Viscosity, ASTM D2161	
@ 100°F, SUS	481
@ 210°F, SUS	62.8
Viscosity Index, ASTM D2270	100
Pour Point, ASTM D97	
°C	-12
(°F)	(10)
Flash Point, ASTM D92	
°C	250
(°F)	(482)
Specific Gravity, ASTM D1298, 60/60°F	0.869
Appearance	Clear
Color	Water-white